Approved For Release 2001/03/05 CIA-RDR82-00457R99749919

INFORMATION REPORT

CD NO.

COUNTRY

Czechoslovakia

CONFIDENTIAL

DATE DISTR 2 May 51

SUBJECT

Characteristics of Sheet Steel Required

by Skode Pilsen

NO. OF PAGES

PLACE ACQUIRED

DATE OF

25X1A

25X1C

NO. OF ENCLS.

SUPFLEMENT TO

25X1A



25X1X

The following is a list of steel sheet imports required by the Skoda Works in Pilsen. This list was furnished by Omnirol to USIA agents.*

Quality according to German Industrial Standards (DIN)	<u>Length</u>	<u>Vidéh</u>	Thickness_	Leight in tong
St. 34,218 with guaranteed	1200	800	30	210
weldability and ductility	5200	800	30	210
				£20
St. 34.21S with guaranteed	1700	1150	8	540
weldability, ductility, and	2600	1020	8 5 6 8 8	90
anti-corrosive properties	1200	650	6	45
	2100	1100	6	54
	2000	1000	8	60
	2300	660	, ජි	120
,	2150	1380	8 5 _	45
	2000	10 00	5 _	108 1062
St. 37.21	5550	3 00	12	16
	2000	1000	8	155
	2000	10 00	5	176
	3000	2500	5 5 5	115
	6000	2800	5	25
	2600	1300	25	35
0.3	2800	2500	25	35
Heemsti ka	6000.	2700	30	30
No Change in Class.	4000	2000	30	30
Declassified	4500	2800	45	45
Class. Changed To: TS S C	4000	1800	25	35
	2950	2850	40	38
Auth.: HR 70-2	4000	2800	40	37
Date: 04 08/28 By: 024_	3000	20 00	50	38
	4000	2000	50	22
	2000 -	1000	6	255

CONFIDENTIAL

	CLASSIFICATIO	ON	SECRIT/CONTROL	U.C. OFTI	CIALS OTH	
STATE X NAVY	X NSEB		DISTRIBUTION			1
ARMY X AIR	FBI		ORR Ev			-

Approved For Release 2001/03/05 : CIA RDR62400457R007400190003-1

Carrie and	SECRET/SOME - U.S. OFFICIALS COM			
CETT AL	INTELLIGENCE	AGETCY		25X1A
	3000 3000 3000 3000 3000 3000 3000 300	1500 1500 1500 1500 1500 1500 1500 1500	67801245605678902345678056780125025635050010	25 72 150 17 170 120 114 103 16 104 203 23 105 24 620 720 105 200 200 200 200 200 200 200 200 200 2
St. 37,21 especially suitable for pressing and forging	2000	1000	5	45
St.37,21S with guaranteed weldability and ductility	2850 2000 3000 3000 3000 3000 3000 3000 30	330 1000 1500 1500 1500 1500 1500 1500 1	5 5 5 6 8 10 12 15 20 25 30 8 10 12 15 25 25	45 60 60 60 60 60 60 60 60 60 67 86 798 47 38 75

Approved For Release 2001/03/05 : CIA-RDP82-00457R007400190003-1

Approved For Release 2001/03/05 : CIA-RDP82-00457R007400190003-1

SECRIT/COURROL - U.F. OFFICIALS ONLY

CENTRAL INTUL		AGENCY	25X1A	,
St. 37.21S with guaranteed weldability and particularly suitable for pressing and forging	2030 3260 920 3000 3000	440 1150 680 1000 1500	6 8 20 10 15	619 36 718 16 24
St. 42.21	2980 9870 2000	1030 870 1000	8 30 5	60 210 69 339
St. 42.21 with guaranteed welda- bility and ductility	4840 3290	2400 610	20 20	282 147 1429
St. 42,21 enti-corrosive	23 1 0 13 1 0	2100 1250	6 5	83 92 175
St. 50.21	900 2500 2500 2500 2500 2500 3000 3000 30	810 1250 1250 1250 1250 1250 1500 1500 15	55 5 10 15 20 25 6 10 12 34 6 10	71 45 45 45 45 45 15 36 83 87 2340 880 600
St.525 with a strength (festigkeit) of 52-64 kg/sq. mm; elasticity of 14-20% at d=10 (sic); a set (beruhigter) steel with a guaranteed tensile strength of 36 kg/sq. rm and quaranteed smaltability and weldability	2000 2500 2500 2500 2500 2500 2500 2500	1000 1250 1250 1250 1250 1250 1250 1250	6 5 6 10 12 15 20 25 30 35 7 14 16	534 45 45 45 45 45 45 45 45 45 45 45 45 45
Boiler plate 1 I	6000 3000 3000 6000 6000 6000	2500 1500 1500 2500 2500 2500	19 14 8 10 11	333 31 73 201 194 102 934

25X1A

CONFIDENTIAL

COOR T/COMPROL -